

Features

- ARM Based HMI
- Fanless design
- Flat front panel touch screen
- TI- AM3354, ARM® Cortex™ A8 processor
- Onboard 512MB DDR3 SDRAM
- Onboard 512MB up to 1GB NAND Flash
- DC 9~36V wide-ranging power input
- LED backlight LCD



Specifications

System

CPU	Ti-AM3354, ARM Cortex A8(1x Core,1.0GHz)
System Chipset	NA
System Memory	Onboard 512MB DDR3 SDRAM

External IO Port

USB	2 x USB 2.0 type A
Serial/Parallel	1 x RS-232/422/485 DB9 , default RS-232
Audio	1 x Line-out
LAN	1 x GbE LAN RJ-45 (POE for option)
Power Connector	1 x 3-pin terminal block connector 1 x 2-pin Power switch connector
Option	TB-508CAN1(Linux only) TB-508C1

Storage Space

HDD	Onboard 512MB NAND Flash (1GB for option)
Movable device	1 x micro SD slot

Expansion

Onboard expansion bus	1 x mini-PCIe slot(full size)
-----------------------	-------------------------------

Display

Display Type	5.6" TFT-LCD
Max. Resolution	640 x 480
Max. Color	262K
Luminance (cd/m²)	350
Viewing Angle (H°/V°)	140 (H) / 120 (V)
Contrast Ratio	500: 1
Backlight Lifetime	20,000 hrs


Touch screen- Resistive Touch

Interface	ADC (Analog-to-Digital Converter)
Light Transmission(%)	Over 80%

Power

Power Input	DC 9~36V
Power Consumption	ARMPAC-505P: 9W

Dimensions



Mechanical

Construction	Plastic front bezel and Chassis
IP rating	IP65 compliant front bezel
Mounting	Panel Mount , VESA mount 75x75
Dimension(mm)	204 x 150 x 43
Net weight(Kg)	0.8

Environmental

Operating Temperature	0~50°C
Storage Temperature	-20~60°C
Storage Humidity	10 to 90% @ 40°C , non-condensing
Certificate	CE/FCC Class A/UL

Operating System Support

Windows Embedded Compact 7, Linux 3.2 / 4.4.12 + QT 4.8.5

ICP Electronics
Australia Pty Ltd

TEL: 02 9457 6011
sales@icp-australia.com.au
www.icp-australia.com.au

