ICP Electronics
Australia Pty Ltd
TEL: 02 9457 6011
sales@icp-australia.com.au
www.icp-australia.com.au

TYPE 10

ICE-DB-T10

Baseboard for COM Express Type 10 Module COM.0 Rev. 2.1, support PICMG EAPI R1.0







Specifications

- Form Factor
  microATX form factor baseboard (244mm x 244mm)
- COM Express type
  Supports COM Express Compact/Mini module using connector pin out Type 10
- Display Interfaces
  1 x eDP
  1 x VGA
  1 x DisplayPort pin-header
- Audio
  Realtek ALC662 HD Audio codec (Line-in, Line-out, Mic)
- Internal I/O Interface
  4 x PCIe x1 — 1 x LPC
  2 x SATA port — 1 x SD card socket
  2 x RS-232 from COM Express (only TX, RX, GND)
- External I/O Interface
  1 x VGA — 1 x Audio jack (Line-in, Line-out, Mic)
  2 x USB 3.1 Gen 1 (5Gb/s) — 6 x USB 2.0
  1 x RJ-45
- Front Audio
  1 x Front audio (2x5 pin)
- TPM
  1 x TPM connector (2x10 pin)
- 80 Port
  1 x 80 port (2x7 segment display)
- Front Panel
  1 x Front panel (2x7 pin, power LED, HDD LED, speaker(Buzzer), power button, reset button)
- I²C
  1 x I²C (1x4 pin)
- SMBus
  1 x SMBus (1x4 pin)
- Internal Storage
  EEPROM (support EAPI R1.0)
- LPC
  1 x LPC
- Fan Connector
  1 x 4-pin / 1 x 3 pin CPU module fan connector
- Watchdog Timer
  Software programmable, support 1~255 sec. system reset
- Power Supply
  ATX / AT power supply
  24+4 pin
- Operating Temperature
  -20°C ~ 60°C
- Storage Temperature
  -30°C ~ 70°C
- Operating Humidity
  5% ~ 95%, non-condensing
- Dimensions
  243.8 mm x 243.8 mm (9.6" x 9.6")
- Weight: GW:550g / NW:350g
- CE/FCC compliant

1.35V DDR3L | Dual Display | USB 3.1 | SATA 3Gb/s | GbE

Features

- mATX form factor baseboard for COM.0 Rev. 2.1, Pin-out Type 10
- Support four PCIe x1
- Support eDP, VGA and iDP
- Support PICMG EAPI R1.0

Dimensions *(Unit: mm)*



Packing List

1 x COM Express Baseboard	1 x SATA cable
1 x Mini jumper pack	1 x QIG

Ordering Information

Part No.	Description
ICE-DB-T10-R10	Baseboard for COM Express Type 10 Module COM.0 Rev. 2.1, support PICMG EAPI R1.0
19800-000082-RS	RS-232/422/485 cable, 14-pin to dual DB-9, 230mm, P=2.54
32102-000100-200-RS	SATA power cable, MOLEX 5264-4P to SATA15P