

VBOX-3120-3S

Intel Haswell Dual Core 2980U 1.6GHz CPU with
3 x RS-232/ DC 9-36V Input In-Vehicle Computer

Features

- Intel Gen4 Dual Core 2980U 1.6GHz
- Wireless support LTE, 3.5G, WLAN, GPS, GSM/GPRS, Bluetooth
- 9V - 36V DC Power Input
- Smarter Vehicle Power Ignition for Variety Vehicle
- 3 x RS-232 (COM1&COM2 with RS-232/422/485)
- 2 x DI / 2 x DO (12V / 100mA)



Power Ignition



Wide Range



Wireless



Battery Backup

Taiwan Patent No. M447854



System	
CPU	Intel Gen4 Dual Core 2980U 1.6 GHz (optional for Core i3/i5/i7)
Memory	1 x DDR3L-1600 SO-DIMM up to 8GB
Graphics	Intel HD Graphics
ATA	2 x Serial ATA 2.0 Ports with 6Gb/s HDD Transfer Rate
LAN Chipset	2 x Intel i210-AT Gigabit Ethernet
Watchdog	1 ~ 255 Level Reset
I/O	
Serial Port	3 x RS-232 (COM1 & COM2 with RS-232/422/485)
USB Port	2 x USB 3.0 and 1 x USB 2.0 Ports
LAN	2 x RJ45 Ports for GbE
Video Port	1 x HDMI and DVI-I*
GPIO Port	2 In and 2 Out (12V / 100mA)
Audio	Mic-in/Line-out
Expansion Bus	3 x Mini-card Slots
Antenna	4 x SMA-type External Antenna Connectors for LTE / WLAN/ UMTS / GSM / GPRS / GPS / Bluetooth
SIM Card Socket	2 x SIM Card Sockets Supported Onboard with eject
	*Use only with Single Link DVI Cables.
Power Requirement	
Power Input	9V - 36V DC Power Input
Power Management	Vehicle Power Ignition for Variety Vehicle
Power Off Control	Power off Delay Time Setting by BIOS and Software
Battery(UPS)	Internal Battery Kit for 10 Mins Operating (Optional) Patent No. : M447854 - Build-in Battery
Qualification	
Certifications	CE, FCC Class A, E-13

Storage	
Type	1 x 2.5" Drive Bay for SATA Type Hard Disk Drive / SSD 1 x SATA DOM
Software	
Operating System	Windows 7, WES 7, Windows 8.1, Linux 3.0.X
Environmental	
Operating Temp.	-40 ~ 70°C (SSD), ambient w/ 0.6m/s airflow
Storage Temp.	-40 ~ 80°C
Relative Humidity	10 ~ 90% (non-condensing)
Vibration (random)	2.5g@5~500 Hz with SSD
Vibration Operating	MIL-STD-810G, Method 514.5, Category 20, Ground Vehicle-Highway
Truck Storage	MIL-STD-810G, Method 514.5, Category 24, Integrity Test
Shock	Operating: MIL-STD-810G, Method 516.5, Procedure I, Trucks and semi-trailers=15G (11ms) with SSD
Crash Hazard	MIL-STD-810G, Method 516.5, Procedure V, Ground equipment=100g
Mechanical	
Construction	Aluminum Alloy
Mounting	Wall-mount, VESA-mount, Din Rail Mounting Kit
Weight	1406 g
Dimensions	182 x 167.6 x 54 mm
Ordering Information	
Part Number	763120010006
Description	Intel Haswell Dual Core 2980U 1.6GHz CPU w/ 3 x RS-232/ DC 9-36V Input In-Vehicle Computer
State of Origin	Made in Taiwan

ICP Electronics
Australia Pty Ltd

TEL: 02 9457 6011
sales@icp-australia.com.au
www.icp-australia.com.au

