




**Features**

- PCIe 2.0 compliant. RS-232/422/485 mode configurable by software
- Up to 1 Mbps RS232 and 15 Mbps RS422/485 serial data rate. 16C550 compatible. 256-byte FIFOs
- Alternative vertical or horizontal connector
- Full RS-232 functions with DB9 connector
- Termination resistor enabled/disabled by DIP switch
- Complies with EN61000-4-2 (ESD) Air-15kV, Contact-8kV
- Industrial temperature -40 °C to 85 °C
- 30μ" golden finger, 3-year warranty
- Industrial design, manufactured in innodisk Taiwan

Mechanical Drawing**EGP2-X401-W1 (Vertical Connector)****EGP2-X401-W2 (Horizontal Connector)**

DIP Switch Setting	
OFF	Normal
ON	Termination

DB9 Pin define			
Pin	RS-232	RS-485	RS-485
		full duplex	half duplex
1	DCD	TX-	D-
2	RX	TX+	D+
3	TX	RX+	
4	DTR	RX-	
5	GND	GND	GND
6	DSR		
7	RTS		
8	CTS		
9	RI		

Specifications**Headquarters (Taiwan)**

5F., No.237, Sec. 1, Datong Rd.,
Xizhi Dist., New Taipei City 221,
Taiwan

Tel: +886-2-7703-3000
Email: sales@innodisk.com

Branch Offices:**USA**

usasales@innodisk.com
+1-510-770-9421

Europe

eusales@innodisk.com
+31-40-3045-400

Japan

jpsales@innodisk.com
+81-3-6667-0161

China

sales_cn@innodisk.com
+86-755-2167-3689

www.innodisk.com

© 2018 Innodisk Corporation.
All right reserved. Specifications
are subject to change without
prior notice.

October 1, 2018

Order information

EGP2-X401-W1(Vertical connector, Wide Temp.)

EGP2-X401-W2(Horizontal connector, Wide Temp.)

M.2 2242 to four RS232/422/485 Module

ICP Electronics
Australia Pty Ltd

TEL: 02 9457 6011
sales@icp-australia.com.au
www.icp-australia.com.au