



GPS-721U-MRTU

56-channel GPS Receiver with 1-channel Digital Output and 1-channel PPS Output plus Active External GPS Antenna

Features

- 56-channel GPS Receiver
- RS-485 Interface supports either the DCON or the Modbus RTU Protocol
- RS-232 supports the NMEA 0183 v3.0 Format, as well as either the DCON or Modbus RTU Protocol
- 1-channel Digital Output, 1-channel PPS Output (1 pulse/s), RS-485, and RS-232 Interfaces
- PPS: 100 ms pulse/s output for precise timekeeping and time measurement
- Fully compatible with SBAS (WAAS, EGNOS, MSAS)



Introduction

The GPS-721U-MRTU module provides high sensitivity and low power consumption with an ultra small form factor. The GPS module is powered by a u-blox solution and provides superior sensitivity and performance, even in an urban environment, or an environment that features dense foliage.

Applications

- Satellite Time Correction
- Personal Positioning and Navigation
- Automotive Navigation
- Marine Navigation

I/O Specifications

Digital Output	
Channels	1 (Sink)
Type	Non-isolated Open Collector
Current	100 mA
Load Voltage	+5 VDC ~ +30 VDC

System Specifications

GPS Receiver	
Chip	u-blox Solution
Frequency	L1 1575.42 MHz, C/A Code
Channels	56
Position Accuracy	Autonomous: 2.5 m SBAS: 2.0 m
Max. Altitude	< 50000 m
Max. Velocity	< 500 m/s
Acquisition Time	Cold Start (Open Sky) = 29 s (Typical)
Sensitivity	Tracking: Up to -161 dBm Cold start: Up to -148 dBm
Protocol Support	NMEA 0183 version 2.3 (compatible to 3.0)
GPS Output	
PPS	1 pulse per second output (Default 100 ms pulse/sec)
RS-232 Interface	GPS Data Output
LED Indicators	
Power/Communication	1
GPS	3
Power	
Protection	Power Reverse Polarity Protection
Frame Ground for ESD Protection	Yes
Required Supply Voltage	+10 VDC ~ +30 VDC (Non-regulated)
Power Consumption	0.8 W
Mechanical	
Dimensions (L x W x H)	117 mm x 72 mm x 35 mm
Environment	
Operating Temperature	-25 to +75°C
Storage Temperature	-40 to +85°C
Humidity	5 to 95% RH, Non-condensing

